

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 1 of 13

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Mineral Spirits**

Other means of identification : None reported.

Recommended use of the chemical and restrictions on use

: Industrial solvent.
Use pattern: Professional Use Only
Restriction on use: None known

Chemical family : Petroleum distillates

Name, address, and telephone number
of the supplier:

Comet Chemical Company Ltd.

3463 Thomas Street
Innisfill, ON, Canada
L9S 3W4

Supplier's Telephone # : (705) 436-5580

24 Hr. Emergency Tel # : GFL Environmental - 1-888-772-2543

Name, address, and telephone number of
the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear colourless liquid. Petroleum hydrocarbon odour.

Most important hazards: Causes skin irritation. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Occupational exposure to the substance or mixture may cause adverse effects.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Hazard classification:

Flammable Liquids - Category 3

Skin Irritation - Category 2

Specific target organ toxicity, single exposure - Category 3 (narcotic effects)

Specific Target organ toxicity, repeated exposure - Category 1

Aspiration toxicity: Category 1

Label elements

Hazard pictogram(s)



Signal Word

DANGER!

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 2 of 13

SAFETY DATA SHEET

Hazard statement(s)

Flammable liquid and vapor.
Causes skin irritation.
May cause drowsiness and dizziness.
Causes damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

Precautionary statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical and ventilating equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Do not breathe mist or vapor.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves and eye/face protection.

Get medical advice/attention if you feel unwell.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
Wash contaminated clothing before reuse.
If skin irritation occurs: Get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
If swallowed: Immediately call a poison center/doctor.
Do NOT induce vomiting.
In case of fire: Use water fog, dry chemical, CO2 or 'alcohol' foam to extinguish.

Store locked up.
Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Other hazards which do not result in classification:
Ingestion may cause irritation of the mouth, throat and stomach. May cause respiratory irritation. Contact with eyes may cause irritation.

Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Environmental precautions:
Avoid release to the environment. Toxic to aquatic life with long lasting effects. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance with impurities

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Stoddard solvent (mineral spirits)	Mineral spirits; White spirits; High flash naphtha	8052-41-3	100.00

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 3 of 13

SAFETY DATA SHEET

Hydrotreated light distillate	Distillates (petroleum), hydrotreated light	64742-47-8	100.00
Trimethylbenzenes (mixed isomers)	Trimethylbenzene (mixed isomers) Methylxylenes	25551-13-7	Trace
Xylenes	Dimethylbenzene; Methyltoluene; Xylol	1330-20-7	Trace
Cumene	Not available.	98-82-8	Trace
Ethylbenzene	Ethylbenzol Phenylethane	100-41-4	Trace

Note: that this product may contain either of the above mentioned CAS numbers.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : If swallowed: Immediately call a poison center/doctor. Do not induce vomiting. Rinse mouth thoroughly. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Call a POISON CENTER or doctor/physician if you feel unwell.
- Skin contact* : Wash affected areas with soap and water. Take off contaminated clothing and wash before re-use. Get medical attention if irritation develops and persists.
- Eye contact* : Flush with large amounts of water for 15 minutes. Remove contact lenses, if present and easy to do. If irritation or symptoms develop, seek medical attention.

Most important symptoms and effects, both acute and delayed

- : Causes skin irritation. Symptoms may include redness, edema, drying defatting and cracking of the skin. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. May cause respiratory irritation. May cause headache, nausea, dizziness and other symptoms of central nervous system depression. May cause central nervous system effects. Symptoms may include coughing, choking and wheezing. Direct eye contact may cause temporary redness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May have laxative effects.

Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically. Aspiration hazard. This product is a CNS depressant. .

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

- Suitable extinguishing media* : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media* : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Flammable liquid and vapour. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Vapour can travel considerable distance and flashback to a source of ignition. Vapours are heavier than air and collect in confined and low-lying areas.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Liquids - Category 3

Hazardous combustion products

- : Carbon dioxide and carbon monoxide. Other unidentified organic compounds. .

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 4 of 13

SAFETY DATA SHEET

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. A full-body chemical resistant suit should be worn. Do not enter without wearing specialized protective equipment suitable for the situation. Firefighter's normal protective clothing (Bunker Gear) will not provide adequate protection. A full-body encapsulating chemical protective suit with positive pressure self-contained breathing apparatus (NIOSH approved or equivalent) may be necessary.

Special fire-fighting procedures

- : Evacuate personnel to safe areas. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Dike for water control. Avoid release to the environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.

Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up

- : Ventilate the area. Prevent further leakage or spillage if safe to do so. Dike for water control. Use only non-sparking tools and equipment in the clean-up process. Spilled material will create slippery surfaces. Clean up promptly. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contact the proper local authorities.

Special spill response procedures

- : In Canada: For 24-hour emergency assistance, call: 1-613-996-6666 (CANUTEC). US CERCLA Reportable quantity (RQ): None reportable.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Use only outdoors or in a well-ventilated area. Wear suitable protective equipment. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep away from heat and open flames. - No smoking. Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting/equipment. Take precautionary measures against static discharges. Bond and ground transfer containers and equipment to avoid static accumulation. Label containers appropriately. Wash thoroughly after handling. Keep containers closed when not in use.

Conditions for safe storage : Store locked up. Store in a cool, dry, well-ventilated area. Keep container tightly closed. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks.

Incompatible materials : Strong oxidizers (e.g. Chlorine, Peroxides, etc.).

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 5 of 13

SAFETY DATA SHEET

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>				
<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Stoddard solvent (mineral spirits)	100 ppm	N/Av	500 ppm ; 2900 mg/m ³	N/Av
Hydrotreated light distillate	200 mg/m ³ (as total hydrocarbon vapour)	N/Av	N/Av	N/Av
Trimethylbenzenes (mixed isomers)	25 ppm	N/Av	25 ppm (final rule limit)	N/Av
Xylenes	100 ppm	150 ppm	100 ppm (435 mg/m ³)	N/Av
Cumene	50 ppm	N/Av	50 ppm (245 mg/m ³) (Skin)	N/Av
Ethylbenzene	20 ppm	N/Av	100 ppm (435 mg/m ³)	N/Av

Exposure controls

Ventilation and engineering measures

: Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapours below their respective threshold limit value. Use explosion-proof electrical and ventilating equipment.

Respiratory protection

: Respiratory protection is required if the concentrations exceed the TLV. Use a NIOSH approved dust respirator if dust levels exceed exposure limits. Seek advice from respiratory protection specialists.

Skin protection

: Wear protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection

: Wear eye/face protection. Chemical safety glasses with side shields or splash proof goggles.

Other protective equipment

: Wear appropriate protective clothing to prevent skin contact, such as coveralls or long sleeved shirt, long pants, and shoes and socks. An eyewash station and safety shower should be made available in the immediate working area. Other equipment may be required depending on workplace standards.

General hygiene considerations

: Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	: Liquid.
Colour	: Clear, colorless.
Odour	: Mild petroleum odour.
Odour threshold	: No information available.
pH	: No information available.
Melting Point/Freezing point	: -58°C(-72.4°F)
Initial boiling point and boiling range	: 157-218°C (314.6-424.4°F)

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 6 of 13

SAFETY DATA SHEET

Flash point : 42°C
Flashpoint (Method) : closed cup
Evaporation rate (BuAe = 1) : No information available.
Flammability : Not applicable.
Lower explosion or flammability limit (% by vol.)
: 0.6%
Upper explosion or flammability limit (% by vol.)
: 8%
Oxidizing properties : None known.
Explosive properties : Not explosive
Vapour pressure : 0.22 mm Hg
Relative vapour density : 4.5
Relative density / Specific gravity
: 0.79g/cm3
Solubility in water : Insoluble.
Other solubility(ies) : No information available.
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution
: Not available.
Auto-ignition temperature : 230°C (446°F)
Decomposition temperature : No information available.
Viscosity : No information available.
Particle characteristics : Not applicable.
Volatiles (% by weight) : No information available.
Volatile organic Compounds (VOC's)
: No information available.
Absolute pressure of container
: N/Ap
Flame projection length : N/Ap
Other physical/chemical comments
: None known or reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions
: Hazardous polymerization does not occur.
Conditions to avoid : Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials.
Incompatible materials : Strong oxidizing agents; Strong acids; Strong alkalis
Hazardous decomposition products
: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 7 of 13

SAFETY DATA SHEET

Routes of exposure skin absorption

: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: May cause respiratory tract irritation. Symptoms may include coughing, choking and wheezing.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed - can enter lungs and cause damage. Aspiration may cause pulmonary oedema and pneumonitis.

Sign and symptoms skin

: Causes skin irritation. Symptoms may include redness, edema, drying defatting and cracking of the skin.

Sign and symptoms eyes

: Direct eye contact may cause slight redness.

Potential Chronic Health Effects

: Prolonged exposure can cause redness, swelling, itching, cracking of the skin, dermatitis and sensitization.

Mutagenicity

: Not expected to be mutagenic in humans.

Carcinogenicity

: This material is not classified as hazardous under U.S. OSHA regulations (29 CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Contains Cumene. Cumene is classified as possibly carcinogenic by IARC (Group 2B). Ethylbenzene is classified as possibly carcinogenic by IARC (Group 2B) and the ACGIH (Category A3).

Reproductive effects & Teratogenicity

: Not expected to have other reproductive effects.

Sensitization to material

: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Specific target organ toxicity, single exposure Category 3
May cause drowsiness and dizziness.

Specific Target organ toxicity, repeated exposure - Category 1
Causes damage to organs through prolonged or repeated exposure.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye and respiratory disorders.

Synergistic materials

: No information available.

Toxicological data

: See below for toxicological data on the substance.

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 8 of 13

SAFETY DATA SHEET

<u>Chemical name</u>	<u>LC₅₀(4hr)</u> <u>inh, rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Stoddard solvent (mineral spirits)	>5.5 mg/L	>5000 mg/kg	>3000 mg/kg
Hydrotreated light distillate	>6.03 mg/L (aerosol)	>5000 mg/kg	>2000 mg/kg
Trimethylbenzenes (mixed isomers)	18 - 24 mg/L (vapour)	8970 mg/kg	> 3160 mg/kg
Xylenes	6350 ppm (27.6 mg/L) (vapour)	3253 mg/kg	12 180 mg/kg
Cumene	8000 ppm (39 mg/L) (vapour)	2260 mg/kg	10 627 mg/kg
Ethylbenzene	4000 ppm (17.4 mg/L) (vapour)	3500 mg/kg	15 380 mg/kg

Other important toxicological hazards

: See Section 2 for additional information.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity

 : Toxic to aquatic life with long lasting effects. .
 The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	<u>CAS #</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Stoddard solvent (mineral spirits)	8052-41-3	2.1- 4.2 mg/L (Bluegill sunfish)	N/Av	None.
Hydrotreated light distillate	64742-47-8	45 mg/L (Fathead minnow)	N/Av	None.
Trimethylbenzenes (mixed isomers)	25551-13-7	7.72 mg/L (Fathead minnow) (Read-across)	N/Av	None.
Xylenes	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
Cumene	98-82-8	4.8 mg/L (Rainbow trout)	N/Av	None.
Ethylbenzene	100-41-4	4.2 mg/L (Rainbow trout)	1.13 mg/L (30 days) (QSAR)	None.

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 9 of 13

SAFETY DATA SHEET

<u>Ingredients</u>	CAS #	<u>Toxicity to Daphnia</u>		
		<u>EC50 / 48h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Stoddard solvent (mineral spirits)	8052-41-3	0.42-2.3mg/L Water flea	0.1-0.37 mg/L Water flea	1
Hydrotreated light distillate	64742-47-8	N/Av	N/Av	N/Av
Trimethylbenzenes (mixed isomers)	25551-13-7	2.7 mg/L (Daphnia magna) (Read-across)	0.4 mg/L (Read-across)	None.
Xylenes	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
Cumene	98-82-8	4 mg/L/24hr (Daphnia magna)	N/Av	None.
Ethylbenzene	100-41-4	1.81 mg/L (Daphnia magna)	N/Av	None.

<u>Ingredients</u>	CAS #	<u>Toxicity to Algae</u>		
		<u>EC50 / 96h or 72h</u>	<u>NOEC / 96h or 72h</u>	<u>M Factor</u>
Stoddard solvent (mineral spirits)	8052-41-3	0.58 - 1.2 mg/L/72 hours (Green alga)	0.16 mg/L (Green alga)	1
Hydrotreated light distillate	64742-47-8	N/Av	N/Av	N/Av
Trimethylbenzenes (mixed isomers)	25551-13-7	5.7 mg/L/72hr (Green algae) (Read-across)	0.38 mg/L/72hr (Read-across)	None.
Xylenes	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
Cumene	98-82-8	2.6 mg/L/72hr (Green algae)	N/Av	None.
Ethylbenzene	100-41-4	3.6 mg/L/96hr (Green algae)	3.4 mg/L/96hr	None.

Persistence and degradability

: Not readily biodegradable.

Bioaccumulation potential

: No data is available on the product itself.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Stoddard solvent (mineral spirits) (CAS 8052-41-3)	3.16-7.06	N/Av
Hydrotreated light distillate (CAS 64742-47-8)	5.1-8.8	N/Av
Trimethylbenzenes (mixed isomers) (CAS 25551-13-7)	3.63	42 - 328 (common carp)
Xylenes (CAS 1330-20-7)	3.12 - 3.2	50 - 58
Cumene (CAS 98-82-8)	3.55	224 (calculated)
Ethylbenzene (CAS 100-41-4)	3.15	1.1 - 1.5

Mobility in soil

: This material has low solubility and floats, and is expected to migrate from water to the land.

Other Adverse Environmental effects

: No data is available on the product itself.

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024








Page 10 of 13

SAFETY DATA SHEET

SECTION 13. DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle waste according to recommendations in Section 7. Empty containers may contain hazardous residues.
- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations.
- RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	UN1268	PETROLEUM PRODUCTS, N.O.S.	3	III	 
TDG Additional information	The environmentally hazardous substance mark must appear on packagings holding more than 5 litres of the material. May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
49CFR/DOT	UN1268	Petroleum distillates, n.o.s.; or Petroleum products, n.o.s.	3	III	
49CFR/DOT Additional information	Limited Quantity exemption may be used if product is in containers or 5 Litres or less, per Section 173.150 of 49 CFR.				
IMDG	UN1268	PETROLEUM DISTILLATES, N.O.S.; or PETROLEUM PRODUCTS, N.O.S.	3	III	 
IMDG Additional information	Consult the IMDG regulations for exceptions. The environmentally hazardous substance mark must appear on packagings holding more than 5 litres of the material.				
ICAO/IATA	UN1268	Petroleum products, n.o.s.	3	III	 
ICAO/IATA Additional information	Refer to ICAO/IATA Packing Instruction The environmentally hazardous substance mark must appear on packagings holding more than 5 litres of the material.				

- Special precautions for user** : Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame - No smoking.
- Environmental hazards** : This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:



Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

SAFETY DATA SHEET

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de Minimis Concentration
Stoddard solvent (mineral spirits)	8052-41-3	Yes	N/Ap	N/Av	No	No
Hydrotreated light distillate	64742-47-8	Yes	N/Ap	N/Av	No	No
Trimethylbenzenes (mixed isomers)	25551-13-7	Yes	None.	None.	No	No
Xylenes	1330-20-7	Yes	100 lbs / 45.4 kg	None.	Yes	1%
Cumene	98-82-8	Yes	5000 lb/ 2270 kg	None.	Yes	1%
Ethylbenzene	100-41-4	Yes	1000 lb/ 454 kg	None.	Yes	Yes

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Physical hazards (Flammable)Health hazards (Skin irritation ;Specific target organ toxicity, single exposure ;Aspiration hazard ;Specific target organ toxicity, repeated exposure).

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Stoddard solvent (mineral spirits)	8052-41-3	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Hydrotreated light distillate	64742-47-8	No	N/Ap	No	No	No	No	No	No
Trimethylbenzenes (mixed isomers)	25551-13-7	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Xylenes	1330-20-7	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Cumene	98-82-8	Yes	Cancer	Yes	Yes	Yes	Yes	Yes	Yes
Ethylbenzene	100-41-4	Yes	Cancer	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

All ingredients are present on the DSL.

International Information:

Components listed below are present on the following International Inventory list:

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 12 of 13

SAFETY DATA SHEET

<u>Ingredients</u>	<u>CAS #</u>	<u>European EINECs</u>	<u>Australia AICS</u>	<u>Philippines PICCS</u>	<u>Japan ENCS</u>	<u>Korea KECI/KECL</u>	<u>China IECSC</u>	<u>NewZealand IOC</u>
Stoddard solvent (mineral spirits)	8052-41-3	232-489-3	Present	Present	(9)-1702; (9)-1702	KE-32199	Present	HSR001498
Hydrotreated light distillate	64742-47-8	265-149-8	Present	Present	(9)-1700	KE-12550	Present	No information available.
Trimethylbenzenes (mixed isomers)	25551-13-7	247-099-9	Present	Present	(3)-7; (3)-3427	KE-34408	Present	May be used as a component in a product covered by a group standard, but is not approved for use as a chemical in its own right.
Xylenes	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
Cumene	98-82-8	202-704-5	Present	Present	(3)-32; (3)-22	KE-23957	Present	HSR001184
Ethylbenzene	100-41-4	202-849-4	Present	Present	(3)-60; (3)-28	KE-13532	Present	HSR001151

SECTION 16. OTHER INFORMATION
Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CNS: Central Nervous System
- COC: Cleveland Open Cup
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- EPA: Environmental Protection Agency
- IARC: International Agency for Research on Cancer
- LC: Lethal Concentration
- LD: Lethal Dose
- N/Ap: Not Applicable
- N/Av: Not Available
- NIOSH: National Institute of Occupational Safety and Health
- NTP: National Toxicology Program
- OSHA: Occupational Safety and Health Administration
- PEL: Permissible exposure limit
- SARA: Superfund Amendments and Reauthorization Act
- STEL: Short Term Exposure Limit
- TLV: Threshold Limit Values
- TWA: Time Weighted Average

References

- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices
- 2. ECHA - European Chemical Agency
- 3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases
- 4. Safety Data Sheets from manufacturer.
- 5. US EPA Title III List of Lists
- 6. California Proposition 65 List
- 7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal

Preparation Date (mm/dd/yyyy)

: 03/28/2019

Reviewed Date SDS (dd/mm/yyyy)

: 10/05/2024

Revision No.

: 3



Comet Chemical Company Ltd.
 3463 Thomas Street
 Innisfill, ON, Canada, L9S 3W4
 Telephone: (705) 436 5580

Mineral Spirits

SDS Revision Date (mm/dd/yyyy): 05/10/2024

Page 13 of 13

SAFETY DATA SHEET

Revision Information : 1. IDENTIFICATION 5. FIRE-FIGHTING MEASURES 9. PHYSICAL AND CHEMICAL PROPERTIES 15. REGULATORY INFORMATION

Other special considerations for handling : Provide adequate information, instruction and training for operators.

<p>Prepared for: Comet Chemical Company Ltd. 3463 Thomas Street Innisfill, ON L9S 3W4 Information (M-F 8:00-5:00): 705-436-5580 www.cometchemical.com</p>	
<p>Prepared by: ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by / obtained from Comet Chemical Company Ltd. and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Comet Chemical Company Ltd. expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Comet Chemical Company Ltd.

END OF DOCUMENT